

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 1220  
IDENTITY: KRYSTAL KLEAR GLASS & CRT CLEANER+ 20A      Revision Date: 05/01/03

=====

Section I

-----

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^	Telephone Numbers:
Address: P.O. BOX 12202	Emergency:
	1-419-841-6616
SCOTTSDALE	Information:
State: AZ Zip Code: 85267	800/747-9593

-----

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
2-BUTOXYETHANOL	* 111-76-2	25 PPM	25 PPM	N/A	_____
ETHYL ALCOHOL	64-17-5	1000	1000	N/A	
METHYL ALCOHOL	* 67-56-1	200	200	N/A	
LIQUIFIED PETROLEUM GAS (LPG)	68476-85-7	1000 PPM	1000 PPM	N/A	
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	N/A	Specific Gravity (water=1)	<1.00
Vapor Pressure: 140 PSIG AT 130°F		PH:	9.7± 0.3
Vapor Density(AIR=1)	<1	Evaporation Rate:	<1
Solubility in Water:	APPRECIABLE	(ETHER=1)	
Appearance and Odor:	AEROSOL SPRAY WITH CHARACTERISTIC ODOR		

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used):NON-FLAMMABLE AS DESCRIBED BY 16 CFR 1500.45  
Flammable Limits: LEL: -1.8 UEL: -9.2  
Extinguishing Media: CO2 FOAM OR DRY CHEMICAL  
Special Fire Fighting Procedures: CONTAINERS SHOULD BE COOLED TO PREVENT PRESSURE BUILD-UP.  
Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE.  
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING

