

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2006

Reviewed on 01/04/2006

1 Identification of substance

Trade name: HOT SPOT WHITE

Product code: 0000161202

Manufacturer/Supplier: SEYMOUR OF SYCAMORE
917 Crosby Avenue
Sycamore, IL 60178
(815)-895-9101, www.seymourpaint.com

Information department: Health & Safety Department

Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 if located outside the U.S.



2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

108-88-3	Toluene	21.05%
74-98-6	propane	18.91%
67-64-1	Acetone	17.03%
106-97-8	n-butane	11.11%
7727-43-7	barium sulphate, natural	7.74%
13463-67-7	titanium dioxide	5.39%
64742-89-8	VM&P Naptha	5.11%
108-65-6	PM acetate	1.67%
64742-47-8	Mineral Spirits	1.33%
1330-20-7	xylene (mix)	1.18%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:



Irritant
Extremely flammable

Physical dangers:

Danger! Extremely flammable liquid and vapor in a pressurized container. Vapors may cause flash fire. Keep away from heat, sparks, and flame.
Extremely flammable.
Irritating to eyes, respiratory system and skin.
Vapours may cause drowsiness and dizziness
Keep out of the reach of children.

Effects of short-term overexposure:

Vapors cause irritation to the eyes, nose, throat, skin, and central nervous system. Symptoms may include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (scale 0 - 4):

Health = 1
Fire = 4
Reactivity = 3

HMIS-ratings (scale 0 - 4):

Health= 1
Fire= 4
Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents: CO₂, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2006

Reviewed on 01/04/2006

Trade name: HOT SPOT WHITE**Protective equipment:** No special measures required.

(Contd. of page 1)

6 Accidental release measures

Personal safety**Precautions:**

Wear protective equipment. Keep unprotected persons away.

Environmental safety**Precautions:**Do not allow product to reach sewage systems or ground water.
Inform appropriate authorities in case of seepage into water course or sewage system.**Measures for cleaning/collecting:**

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material.

Do not smoke. Protect from electrostatic charges.

Storage requirements:

Observe pressurized container storage regulations. Consult with your local authorities.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:**74-98-6 propane**

PEL	1800 mg/m ³ , 1000 ppm
REL	1800 mg/m ³ , 1000 ppm
TLV	(4508) mg/m ³ , (2500) ppm

106-97-8 n-butane

REL	1900 mg/m ³ , 800 ppm
TLV	1900 mg/m ³ , 800 ppm

7727-43-7 barium sulphate, natural

PEL	15*; 5** mg/m ³ *Total dust **Respirable fraction
REL	10*; 5** mg/m ³ *Total dust **Respirable fraction
TLV	10 mg/m ³ (e)

108-65-6 PM acetate

WEEL	100 ppm
------	---------

64742-47-8 Mineral Spirits

TLV	200 mg/m ³ As total hydrocarbon vapor; Skin; (P)
-----	--

1330-20-7 xylene (mix)

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm (o-, m-, & p-isomers)
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

Protective hygienic**measures:**

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

USA

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/04/2006

Reviewed on 01/04/2006

Trade name: HOT SPOT WHITE

(Contd. of page 2)

9 Physical and chemical properties:

General Information:

Form:	Aerosol
Color:	According to trade name description in section 1.
Odor:	Solvent
Boiling point/Boiling range:	-44°C (-47°F)
Flash point:	-19°C (-2°F)
Ignition temperature:	365.0°C (689°F)
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees Fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density:	Not determined.
Specific Gravity:	Between 0.77 and 0.90 (Water equals 1.00)
VOC content:	404.4 g/l / 3.37 lb/gl
VOC in weight percent (less acetone):	40.4 %
Solids content:	21.4 %

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Possibility of Hazardous Reactions: No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: Irritant to skin and mucous membranes.

Primary effect on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information: Harmful

12 Ecological information

Other information: This product does not contain any chloroflourocarbons (CFC's), chlorinated solvents, or heavy metals (lead, mercury, cadmium, etc.). No specific ecological data is available for this product.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Empty cans should be recycled.

14 Transport information:

Hazard class:	2.1
Identification number:	N/A
Label	2.1
ADR/RID class:	2 5F Gases
UN-Number:	1950
IMDG Class:	2.1
Packaging group:	II
EMS Number:	F-D,S-U
Marine pollutant:	No
ICAO/IATA Class:	2.1
Propper shipping name:	Aerosols, Flammable Consumer Commodity ORM-D

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 01/04/2006

Reviewed on 01/04/2006

Trade name: HOT SPOT WHITE

(Contd. of page 3)

15 Regulations

SARA Section 355 (extremely hazardous substances):
None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):
1330-20-7 | xylene (mix)

TSCA (Toxic Substances Control Act): All ingredients are listed.

PROPOSITION 65 Chemicals known to cause cancer:
108-88-3 | Toluene
100-41-4 | ethyl benzene

Canadian WHMIS: Class A, B5---Flammable Aerosols
EPA: A= Known human carcinogen B= Probable human carcinogen
C= Possible human carcinogen
D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

1330-20-7 | xylene (mix) | D

IARC: Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.
Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

13463-67-7 | titanium dioxide | 3
1330-20-7 | xylene (mix) | 3

ACGIH TLVs: A1-designates a confirmed human carcinogen.
A2-designates a suspected human carcinogen.
A3-designates an animal carcinogen.
A4-designates "not classifiable as a human carcinogen".

13463-67-7 | titanium dioxide | A4
1330-20-7 | xylene (mix) | A4

NIOSH:
13463-67-7 | titanium dioxide

USDA (United States Department of Agriculture): This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Craig Swafford, Regulatory Affairs. Email: cswafford@seymourpaint.com