

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 211
IDENTITY: KLEEN ALL FOAMING + 20A Revision Date: 03/04/2010

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 7 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 212 + Specific Gravity (water=1) 1.00
Vapor Pressure (mm Hg) 17.5 Melting Point: N/A
Vapor Density (AIR=1) N/A Evaporation Rate: <1
Solubility in Water: 100% (Butyl Acetate=1)
Appearance and Odor: WHITE FOAM, MILD LEMON/AMMONIA ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point (Method Used): NONE Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS
WHEN INDICATED

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING

Section V: REACTIVITY DATA

PRODUCT NUMBER: 211

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F
Incompatibility (Materials to Avoid): NONE

Hazardous Decomposition or Byproducts: OXIDES OF CARBON

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: EXCESSIVE INHALATION MAY CAUSE SLIGHT DIZZINESS. EYES: IRRITATION AND REDDENING. SKIN: SLIGHT IRRITATION. INGESTION: MAY CAUSE NAUSEA, VOMITING.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES. SKIN: WASH COMPLETELY WITH RUNNING WATER. IF IRRITATION PERSISTS, CONSULT PHYSICIAN. INGESTION: INDUCE VOMITING- SEE PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE AN ABSORBENT CLAY MATERIAL OR TOWEL. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES

Waste Disposal Method: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE EMPTY CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: N/A
Ventilation: Local Exhaust:N/A
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves:N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS THOROUGHLY AFTER USE.

□