

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 214
IDENTITY: GLEAM +20A Revision Date: 07/15/2010
-----

Section I
-----

Manufacturer's Name: MAINTENANCE SOLUTIONS\*\*\* ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593
-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include MINERAL SEAL OIL and PROPANE/N-BUTANE.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: N/A Specific Gravity (water=1) 0.95
Vapor Pressure (mm Hg) 46PSI Melting Point: N/A
Vapor Density (AIR=1) 1 Evaporation Rate: <1
Solubility in Water: 63% (Butyl Acetate=1)
Appearance and Odor: WHITE FOAM, LEMON ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point (Method Used): .200F TCC Flammable Limits: LEL:NE UEL: NE
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS
WHEN INDICATED

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

