

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 397
IDENTITY: VANILLA MOON BEAM +12A Revision Date: 08/05/2010

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include ACETONE, ISOPARAFINIC HYDROCARBON, and PROPANE.

Comment:
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: >130 F Specific Gravity (water=1) 0.79
Vapor Pressure (mm Hg) >20 Melting Point: N/A
Vapor Density (AIR=1) >1 Evaporation Rate: >5
Solubility in Water: 35% (Butyl Acetate=1)
Appearance and Odor: CLEAR SPRAY, VANILLA SCENT

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point (Method Used): <100 TCC Flammable Limits: LEL: <2.5 UEL: <7.7
Extinguishing Media: DRY CHEMICAL, ALCOHOL FOAM, AND CO2
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS IS
ALWAYS RECOMMENDED WHEN FIGHTING FIRES.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.
VAPORS CAN BE FLAMMABLE AND FLOW ALONG SURFACES TO DISTANT IGNITION.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 397

=====
Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F
Incompatibility (Materials to Avoid): STRONG ALKALIES. HIGH TEMPERATURES IN
THE PRESENCE OF STRONG BASES & ACIDS. STRONG OXIDIZING AGENTS.
Hazardous Decomposition or Byproducts: CARBON DIOXIDE AND/OR CARBON
MONOXIDE
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: TEMPERATURES ABOVE 120 F

Section VI: HEALTH HAZARD DATA

=====
Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO
Health Hazards (Acute and Chronic):
INHALATION: EXCESSIVE EXPOSURE MAY CAUSE SLIGHT DIZZINESS. EYES: STRONG
IRRITATION REDDENING. SKIN: MILD IRRITATION.

Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR.
EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WATER.
CONTACT PHYSICIAN IF IRRITATION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====
Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH
RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE
AND LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE
CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE
BURSTING.
Other Precautions: NONE

Section VIII: CONTROL MEASURES

=====
Respiratory Protection: NONE
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHEN USING CHEMICAL PRODUCTS
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USE

□