

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 398
IDENTITY: OCEAN BREEZE 12A Revision Date: 08/05/2010

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include ACETONE, ISOPARAFINIC HYDROCARBON, and PROPANE.

Comment:
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: >130 F Specific Gravity (water=1) 0.79
Vapor Pressure (mm Hg) >20 Melting Point: N/A
Vapor Density (AIR=1) >1 Evaporation Rate: >5
Solubility in Water: 35% (Butyl Acetate=1)
Appearance and Odor: CLEAR SPRAY, FRESH SCENT

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point (Method Used): <100 TCC Flammable Limits: LEL: <2.5 UEL: <7.7
Extinguishing Media: DRY CHEMICAL, ALCOHOL FOAM, AND CO2
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS IS
ALWAYS RECOMMENDED WHEN FIGHTING FIRES.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.
VAPORS CAN BE FLAMMABLE AND FLOW ALOND SURGACES TO DISTANT IGNITION.

