

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 534
IDENTITY: MR. MECHANIC Revision Date: 02/19/2010
-----

Section I
-----

Manufacturer's Name:QUEST CHEMICAL CORPORATION Telephone Numbers:
Address: 12255 FM 529 Emergency:
NORTHWOODS INDUSTRIAL PARK 800/255-3924
HOUSTON Information:
State: TX Zip Code:77041 713/8968188
-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include ETHYL ACETATE, ISOPARAFINIC HYDROCARBON, MINERAL SEAL OIL, PETROLEUM DISTILLATES, and PROPANE/N-BUTANE.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 180 Specific Gravity (water=1) 0.83
Vapor Pressure(mm Hg) 30 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: <1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: THIN BROWN LIQUID WITH STRONG SOLVENT ODOR.

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used):+110F TCC Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPRATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

