

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 591
IDENTITY: CEIL-IT I + 20A Revision Date: 08/07/2009

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include ACETONE, ETHYL ALCOHOL, HEPTANE, ISOPARAFINIC HYDROCARBON, PROPANE/N-BUTANE, and TITANIUM DIOXIDE.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 104F Specific Gravity (water=1) 0.88
Vapor Pressure (mm Hg) N/A Melting Point: N/A
Vapor Density (AIR=1) >1 Evaporation Rate: >1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: WHITE SPRAY, HYDROCARBON SOLVENT ODOR.

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point (Method Used): >100F TCC Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
DO NOT PUNCTURE OR INCINERATE CONTAINER. KEEP AWAY FROM HEAT.
EXPOSURE TO TEMPERATURES >120 F MAY CAUSE BURSTING.

