

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 2-625
IDENTITY: Floating Odor Blanket 5 Revision Date: 02/27/2001

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
SCOTTSDALE 800/535-5053 Infotrac
State: AZ Zip Code: 85267 Information: 800/747-9593

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Row 1: Alkylation naptha, heavy, 064741-65-7, N/EST, 3000 PPM, N/EST, 100.

Comment: N/EST=Not Established
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 355-398°F Specific Gravity (water=1) .69
Vapor Pressure(mm Hg) 1.9@100°F Melting Point: N/A
Vapor Density(AIR=1) 5.3 Evaporation Rate: <0.1
Solubility in Water: Negligible (Butyl Acetate=1)
Appearance and Odor: LIGHT COLORED LIQUID, BUBBLEGUM ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used TCC): 125°F Flammable Limits: LEL: 1 UEL: 7
 Extinguishing Media: Use water spray, CO2, dry chemical, or foam
 Special Fire Fighting Procedures: Use fog nozzles if water is used. Cool fire exposed containers with water spray.

Unusual Fire and Explosion Hazards: Closed containers of this product may explode when exposed to excessive heat. this material creates a fire hazard because it floats on water. If possible, try to contain floating material. During a fire, irritatin and highly toxic gases may be generated by thermal decomposition or combustion.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 266

Stability: Unstable: Conditions to avoid:
 Stable: X Keep away from heat, sparks and open flames.
 Incompatability (Materials to Avoid): Strong oxidizers and acids.

Hazardous Decomposition or Byproducts: Toxic oxides of carbon and unidentified Organic compounds.

Hazardous Polymerization: May Occur: Will Not Occur: X

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Eyes: YES Skin: YES Ingestion: YES
 Health Hazards(Acute and Chronic):
 SKIN: WILL CAUSE SEVERE DRYNESS, CRACKING AND IRRITATION. EYES: MODERATE TO SEVERE IRRITATION. INGESTION: NAUSEA, DIZZINESS, GASTROINTESTINAL IRRITATION AND DIARRHEA.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
 Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: PREEEXISTING EYE AND SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

Emergency and First Aid Procedures: SKIN: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH EXPOSED AREAS WITH SOAP AND WATER. GET MEDICAL ATTENTION. INGESTION: GET MEDICAL ATTENTION. DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENTNT ASPIRATION INTO THE LUNGS. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION.

NOTES TO PHYSICIAN: IF MORE THAN 2.0ML/KG HAS BEEN INGESTED AND VOMITING HAS NOT OCCURRED, EMESIS SHOULD BE INDUCED WITH SUPERVISION. KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT ASPIRATION. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS, GASTRIC LAVAGE USING A CUFFED ENDOTRACHEAL TUBE SHOULD BE CONSIDERED.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====

Steps to be Taken in Case Material is Released or Spilled: ELIMINATE ALL SOURCES OF IGNITION. CONTAIN SPILL AND VENTILATE AREA. ABSORB ON INERT MEDIA AND CONTAINERIZE FOR DISPOSAL USING NON-SPARKING TOOLS.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. DO NOT REUSE EMPTY CONTAINER. OFFER DRUM FOR RECYCLING.

Precautions to be Taken in Handling and Storing: STORE IN A COOL DRY AREA. AVOID TEMPERATURES ABOVE 100 F OR BELOW FREEZING.

Other Precautions: N/A

Section VIII: CONTROL MEASURES

=====

Respiratory Protection: N/A

Ventilation: Local Exhaust: ADEQUATE

Mechanical: N/A

Special: N/A

Other: N/A

Protective Gloves: N/A

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

N/A

Work/Hygienic Practices:

WASH HANDS AFTER USE

Section IX: TRANSPORTATION INFORMATION

=====

D.O.T. SHIPPING NAME: Petroleum distillates, n.o.s. (Petroleum naptha)

D.O.T. HAZARD CLASS: 3-Flammable and Combustible liquid

D.O.T. ID NUMBER: UN 1268

D.O.T. PACKING GROUP: III

D.O.T. RQ(lbs): N/AP

OTHER: LABELS REQUIRED: FLAMMABLE LIQUID, DOMESTIC SHIPMENTS OF THIS PRODUCT CAN BE RECLASSIFIED TO A COMBUSTIBLE. SHIPMENT OF NON-BULK CONTAINERS CONTAINING THIS PRODUCT ARE NOT REGULATED.