

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 214  
IDENTITY: GLEAM +20A Revision Date: 01/16/2007

-----

Section I

-----

Manufacturer's Name: MAINTENANCE SOLUTIONS\*\*\* ^ Telephone Numbers:  
Address: P.O. BOX 12202 Emergency:  
800/255-3924  
SCOTTSDALE Information:  
State: AZ Zip Code: 85267 800/747-9593

-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
MINERAL SEAL OIL	64741-44-2	5 MG/M3	5 MG/M3	N/A	_____
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point: N/A Specific Gravity (water=1) 0.95  
Vapor Pressure(mm Hg) 46PSI Melting Point: N/A  
Vapor Density(AIR=1) 1 Evaporation Rate: <1  
Solubility in Water: 75% (Butyl Acetate=1)  
Appearance and Odor: WHITE FOAM, LEMON ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used): .200F TCC Flammable Limits: LEL:NE UEL: NE  
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER  
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS WHEN INDICATED

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

=====

Stability: Unstable: Conditions to avoid: TEMPERATURES ABOVE 120 F  
Stable: X HOT SURFACES  
Incompatibility (Materials to Avoid): STRONG OXIDIZERS, ALKALIES, ACIDS.

Hazardous Decomposition or Byproducts: NONE KNOWN

Hazardous Polymerization: May Occur: Will Not Occur: X  
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

PRODUCT NUMBER: 214

=====  
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards(Acute and Chronic):  
EYES: MAY CAUSE EYE IRRITATION. INHALATION: EXCESSIVE INHALATION MAY CAUSE  
DIZZINESS AND/OR HEADACHE. SKIN: MAY CAUSE LOCALIZED DEFATTING OF SKIN.  
INGESTION: MAY CAUSE NAUSEA AND/OR DIARRHEA.  
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO  
Signs and Symptoms of Exposure: SEE HEALTH HAZARD ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES:  
FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH AFFECTED AREA WITH SOAP AND  
WATER. INGESTION: DRINK SEVERAL GLASSES OF WATER. IN ALL INSTANCES ABOVE,  
CONSULT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====  
Steps to be Taken in Case Material is Released or Spilled: MOP OR WIPE UP  
SPILL. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: WRAP CONTAINER AND PLACE IN TRASH COLLECTION. DO  
NOT PUNCTURE OR INCINERATE CONTAINER.

Precautions to be Taken in Handling and Storing: STORE IN A COOL, DRY  
AREA. KEEP AWAY FROM HEAT, FLAMES, SPARKS, AND TEMPERATURES ABOVE 120F.

Other Precautions: N/A

Section VIII: CONTROL MEASURES

=====  
Respiratory Protection: N/A  
Ventilation: Local Exhaust:ADEQUATE  
Mechanical: N/A Special: N/A  
Other: N/A  
Protective Gloves:N/A  
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.  
Other Protective Clothing or Equipment:  
N/A  
Work/Hygienic Practices:  
WASH HANDS AFTER USE.