

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 379
 IDENTITY: APPLE SENSATION +12A Revision Date: 06/26/2007

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
 Address: P. O. BOX 12202 Emergency:
 800/255-3924
 SCOTTSDALE Information:
 State: AZ Zip Code: 85267 800/747-9593

HMS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
ACETONE	67-64-1	1000 PPM	750 PPM	N/A	___
ISOPARAFINIC HYDROCARBON	64742-47-8	400 PPM	400 PPM		___
PROPANE *	74-98-6	1000 PPM	N/A	N/A	___
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	180	Specific Gravity (water=1)	0.79
Vapor Pressure(mm Hg)	20	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	0	(Butyl Acetate=1)	

Appearance and Odor: CLEAR SPRAY, RED APPLE SCENT

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): <100 TCC Flammable Limits: LEL: NA UEL: NA
 Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
 Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS
 WHENEVER INDICATED

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
 EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 379

=====

Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F

Incompatibility (Materials to Avoid): STRONG ALKALIES. HIGH TEMPERATURES IN THE PRESENCE OF STRONG BASES. ACIDS. STRONG OXIDIZING AGENTS.

Hazardous Decomposition or Byproducts: CARBON DIOXIDE AND/OR CARBON MONOXIDE

Hazardous Polymerization: May Occur: Will Not Occur: X

Conditions to Avoid: TEMPERATURES ABOVE 120 F

Section VI: HEALTH HAZARD DATA

=====

Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO

Health Hazards(Acute and Chronic):
 INHALATION: EXCESSIVE EXPOSURE MAY CAUSE SLIGHT DIZZINESS. EYES: STRONG IRRITATION REDDENING. SKIN: MILD IRRITATION.

Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR.
 EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WATER.
 CONTACT PHYSICIAN IF IRRITATION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

=====

Respiratory Protection: NONE

Ventilation: Local Exhaust: ADEQUATE

Mechanical: N/A Special: N/A

Other: N/A

Protective Gloves: N/A

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHEN USING CHEMICAL PRODUCTS

Other Protective Clothing or Equipment: N/A

Work/Hygiene Practices:
 WASH HANDS AFTER USE