

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 514

IDENTITY: CBC CIRCUIT BOARD CLNR16A

Revision Date: 01/18/2007

=====

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^

Address: P.O. BOX 12202

SCOTTSDALE

State: AZ Zip Code: 85267

Telephone Numbers:

Emergency:

800/255-3924

Information:

800/747-9593

HMIS CODES: REACTIVITY: 2 FLAMMABILITY: 4 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
CARBON DIOXIDE	124-38-9	5000 PPM	5000 PPM	N/A	_____
HEPTANE	142-82-5	400 PPM	400 PPM	N/A	_____
ISOPROPYL ALCOHOL	67-63-0	400 PPM	400 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	156	Specific Gravity (water=1)	0.71
Vapor Pressure(mm Hg)	124	Melting Point:	N/A
Vapor Density(AIR=1)	< 1	Evaporation Rate:	>1
Solubility in Water:	0%	(Butyl Acetate=1)	
Appearance and Odor:	CLEAR WATER WHITE SPRAY, SOLVENT ODOR		

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used): <20 F TCC Flammable Limits: LEL:1.2 UEL: 7.5

Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER

Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE CONTENTS UNDER PRESSURE DO NOT EXPOSE TO TEMPERTATURES ABOVE 120F AS BURTSING COULD OCCUR. MAY DEVELOP FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

