

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 536
IDENTITY: ELECTRA-DRI + 16A Revision Date: 09/17/1999

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 0 HEALTH: 2 PERSONAL PROTECT: C

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 7 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN
TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 165 Specific Gravity (water=1) 1.38
Vapor Pressure(mm Hg) 100 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: 6
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: BROWN TO AMBER COLOR, CHLORINATED SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used): NONE Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: CO2,
Special Fire Fighting Procedures: NONE

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS.

=====
Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): NONE

Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY
PRODUCE PHOSGENE, CARBON MONOXIDE AND HYDROGEN CHLORIDE GASES.
Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

=====
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS. PROLONGED EXPOSURE MAY LEAD TO UNCONSCIOUSNESS.
EYES: STRONG IRRITATION. SKIN: MILD IRRITATION. MAY CAUSE LOCALIZED
DEFATTING OF SKIN. INGESTION: NAUSEA, VOMITTING, UNCONSCIOUSNESS OR DEATH.
Carcinogenicity: NTP: YES IARC Monographs: Yes OSHA Reg: Yes
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE
WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES:
FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH IMMEDIATELY WITH SOAP AND WATER
AND CONTACT PHYSICIAN IF IRRITATION PERSISTS. INGESTION: CONSULT PHYSICIAN
IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====
Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG
OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO
NOT REUSE EMPTY CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT STORE NEAR HEAT
OR OPEN FLAME. STORE IN A COOL DRY AREA. EXPOSURE TO TEMPERATURES ABOVE
120 F MAY CAUSE BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

=====
Respiratory Protection: ONLY WHEN TLV IS EXCEEDED
Ventilation: Local Exhaust: YES
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: CHEMICAL RESISTANT GLOVES RECOMMENDED.
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
APRON
Work/Hygienic Practices:
WASH HANDS AFTER USE.