

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 537  
IDENTITY: E-Z GLIDE + 16A Revision Date: 01/18/2007

=====

Section I

-----

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^	Telephone Numbers:
Address: P.O. BOX 12202	Emergency:
	800/255-3924
SCOTTSDALE	Information:
State: AZ Zip Code: 85267	800/747-9593

-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 0 HEALTH: 2 PERSONAL PROTECT: C

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name		Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
CARBON DIOXIDE		124-38-9	5000 PPM	5000 PPM	N/A	_____
TETRACHLOROETHYLENE	*+	127-18-4	25 PPM	50 PPM	N/A	_____
TRICHLOROETHYLENE	*+	79-01-6	100PPM	50PPM	N/A	_____
_____		_____	_____	_____	_____	_____
_____		_____	_____	_____	_____	_____
_____		_____	_____	_____	_____	_____
_____		_____	_____	_____	_____	_____
_____		_____	_____	_____	_____	_____

=====

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	165	Specific Gravity (water=1)	1.46
Vapor Pressure(mm Hg)	100	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	0%	(Butyl Acetate=1)	
Appearance and Odor:	CLEAR SPRAY, CHLORINATED SOLVENT ODOR		

=====

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used): NONE	Flammable Limits: LEL: N/A	UEL: N/A
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER		
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS		

=====

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

