

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 538
IDENTITY: DRI-SLIDE + 16A Revision Date: 01/18/2007
-----

Section I
-----

Manufacturer's Name: MAINTENANCE SOLUTIONS\*\*\* ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593
-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include ACETONE, HEPTANE, and PROPANE/N-BUTANE.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: <200 F Specific Gravity (water=1) 0.76
Vapor Pressure(mm Hg) 36 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: >1
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: CLEAR SPRAY, SLIGHT SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used): <5 F TCC Flammable Limits: LEL:1.3 UEL: 10.2
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA PRODUCT NUMBER: 538
=====

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120F, HOT SURFACES
Incompatibility (Materials to Avoid): STRONG OXIDIZERS

Hazardous Decomposition or Byproducts: SILICON DIOXIDE, FORMALDEHYDE,
CARBON OXIDES.

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid:

Section VI: HEALTH HAZARD DATA

=====  
Routes of Entry: Inhalation: YES Skin: YES Ingestion:NO  
Health Hazards(Acute and Chronic):  
INHALATION: DIZZINESS. PROLNGED EXPOSURE MAY LEAD TO UNCONSCIOUSNESS. EYES:  
MILD IRRITATION. SKIN: MAY CAUSE MILD IRRITATION OR LOCALIZED DEFATTING  
OF SKIN.  
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO  
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SEEK  
PHYSICIAN IF BREATHING TROUBLE PERSISTS. EYES: FLUSH WITH WATER FOR 15  
MINUTES. SEEK PHYSICIAN IF IRRITATION PERSISTS. SKIN: WASH AFFECTED AREA  
WITH SOAP AND WATER. SEEK PHYSICIAN IF IRRITAION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====  
Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG  
OR USE ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND  
LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE  
CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT STORE OR USE NEAR  
HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE BURSTING.

Other Precautions: MAY ACCUMULATE AND CREATE A FLAMMABLE ATMOSPHERE

Section VIII: CONTROL MEASURES

=====  
Respiratory Protection: N/A  
Ventilation: Local Exhaust:ADEQUATE  
Mechanical: N/A Special: N/A  
Other: N/A  
Protective Gloves:N/A  
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.  
Other Protective Clothing or Equipment:  
N/A  
Work/Hygienic Practices:  
WASH HANDS THOROUGHLY AFTER USE.