

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 581
IDENTITY: CLEAR LUBE II + 20A Revision Date: 01/26/2007
-----

Section I
-----

Manufacturer's Name: MAINTENANCE SOLUTIONS\*\*\* ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/255-3924
800/747-9593
-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 7 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 156 Specific Gravity (water=1) 0.75
Vapor Pressure(mm Hg) 124 Melting Point: N/A
Vapor Density(AIR=1) 1 Evaporation Rate: 6
Solubility in Water: 0 % (Butyl Acetate=1)
Appearance and Odor: TACKY GELLED LUBRICANT. SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used): <20 F TCC Flammable Limits: LEL:1.1 UEL: 7.5
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A
FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 581

Stability: Unstable: Conditions to avoid: TEMPERATURES ABOVE 120 F

Stable: X

Incompatibility (Materials to Avoid): NONE KNOWN

Hazardous Decomposition or Byproducts: NONE KNOWN

Hazardous Polymerization: May Occur: Will Not Occur: X

Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards(Acute and Chronic):

INHALATION: DIZZINESS-PROLONGED MAY LEAD TO UNCONSCIOUSNESS. EYES: STRONG IRRITATION. SKIN: MILD IRRITATION. MAY CAUSE LOCALIZED DEFATTING.

INGESTION: NAUSEA, DIZZINESS, VOMITING, INTESTINAL CRAMPING

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONTACT PHYSICIAN IF IRRITATION PERSISTS. INGESTION: CONSULT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAMES. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREA.

Ventilation: Local Exhaust: ADEQUATE

Mechanical: N/A

Special: N/A

Other: N/A

Protective Gloves: N/A

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

N/A

Work/Hygienic Practices:

WASH HANDS AFTER USE.