

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 591  
IDENTITY: CEIL-IT I + 20A Revision Date: 01/21/2007

-----

Section I

-----

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^	Telephone Numbers:
Address: P.O. BOX 12202	Emergency:
SCOTTSDALE	800/255-3924
State: AZ Zip Code: 85267	Information:
	800/747-9593

-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
ACETONE	67-64-1	1000 PPM	750 PPM	N/A	_____
ISOPARAFINIC HYDROCARBON	64742-47-8	400 PPM	400 PPM		_____
ISOPROPYL ALCOHOL	67-63-0	400 PPM	400 PPM	N/A	_____
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	_____
TITANIUM DIOXIDE	13463677	5 MG/M3	10 MG/M3	N/A	_____
TRICHLOROETHYLENE	*+ 79-01-6	100PPM	50PPM	N/A	_____

-----

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

-----

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	104	Specific Gravity (water=1)	1.15
Vapor Pressure(mm Hg)	N/A	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	0%	(Butyl Acetate=1)	

Appearance and Odor: WHITE SPRAY, CHLORINATED SOLVENT ODOR.

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used):>100F TCC Flammable Limits: LEL:N/A UEL: N/A  
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER  
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CONTAINER. KEEP AWAY FROM HEAT. EXPOSURE TO TEMPERATURES >120 F MAY CAUSE BURSTING.

