

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 802  
IDENTITY: KLEEN CARB 16A Revision Date: 01/21/2007

=====

Section I

-----

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^	Telephone Numbers:
Address: P.O. BOX 12202	Emergency:
SCOTTSDALE	800/255-3924
State: AZ Zip Code: 85267	Information:
	800/747-9593

-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 2 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
ACETONE	67-64-1	1000 PPM	750 PPM	N/A	_____
CARBON DIOXIDE	124-38-9	5000 PPM	5000 PPM	N/A	_____
ISOPARAFINIC HYDROCARBON	64742-47-8	400 PPM	400 PPM		_____
METHYL ALCOHOL *	67-56-1	200 PPM	250 PPM	N/A	_____
XYLENE(XYLOL) *	1330-20-7	100 PPM	100 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

=====

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point:	147	Specific Gravity (water=1)	0.81
Vapor Pressure(mm Hg)	130	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	3.5
Solubility in Water:	45%	(Butyl Acetate=1)	

Appearance and Odor: CLEAR SPRAY, STRONG SOLVENT SCENT

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used):53F TCC Flammable Limits: LEL:1.8 UEL: 10.0  
Extinguishing Media: CO2, FOAM, WATER, DRY CHEMICAL  
Special Fire Fighting Procedures: SELF CONTIANED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE.  
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

