

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: 823

IDENTITY: DETECT

+ 20A

Revision Date: 01/26/2007

=====

Section I

-----

Manufacturer's Name: MAINTENANCE SOLUTIONS\*\*\* ^

Address: P.O. BOX 12202

SCOTTSDALE

State: AZ Zip Code: 85267

Telephone Numbers:

Emergency:

800/255-3924

Information:

800/747-9593

-----

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
2-BUTOXY ETHANOL *	111-76-2	25 PPM	20 PPM	N/A	_____
ISOPROPYL ALCOHOL	67-63-0	400 PPM	400 PPM	N/A	_____
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

Boiling Point: 212+ Specific Gravity (water=1) 0.99

Vapor Pressure(mm Hg) 18 Melting Point: N/A

Vapor Density(AIR=1) 1 Evaporation Rate: .1

Solubility in Water: 100% (Butyl Acetate=1)

Appearance and Odor: YELLOW FOAM, MILD AMMONIA ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used):NONE Flammable Limits: LEL:N/A UEL: N/A

Extinguishing Media: CO2, WATER FOG, FOAM, WATER

Special Fire Fighting Procedures: NONE.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 823

Stability: Unstable: Conditions to avoid:  
Stable: X TEMPERATURES ABOVE 120 F  
Incompatibility (Materials to Avoid): NONE

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X  
Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards(Acute and Chronic):  
INHALATION: EXCESSIVE INHALATION MAY CAUSE SLIGHT DIZZINESS. EYES:  
IRRITATION, REDDENING. SKIN: SLIGHT IRRITATION. INGESTION: NAUSEA, VOMITING

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO  
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES:  
FLUSH WITH RUNNING WATER FOR 15 MINUTES. SKIN: WASH THOROUGHLY WITH RUNNING  
WATER. CONTACT PHYSICIAN IF IRRITATION PERSISTS. INGESTION: INDUCE VOMITING  
SEE PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG  
OR USE SOME ABSORBENT CLAY MATERIAL OR TOWEL. DISPOSE OF IN ACCORDANCE  
WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT  
REUSE CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR  
HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE  
BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: N/A  
Ventilation: Local Exhaust:N/A  
Mechanical: N/A Special: N/A  
Other: N/A  
Protective Gloves:N/A  
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.  
Other Protective Clothing or Equipment:  
N/A  
Work/Hygienic Practices:  
WASH HANDS AFTER USE.